

PRODUCT-DETAILS

A1N 125 TMF 40-400 3p F F

A1N 125 TMF 40-400 3p F F



| General Information   |                                                                                                           |
|-----------------------|-----------------------------------------------------------------------------------------------------------|
| Extended Product Type | A1N 125 TMF 40-400 3p F F                                                                                 |
| Product ID            | 1SDA066725R1                                                                                              |
| EAN                   | 8015644694098                                                                                             |
| Catalog Description   | A1N 125 TMF 40-400 3p F F                                                                                 |
| Long Description      | C.BREAKER FORMULA A1N 125 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 40-400 A |

| Circular Value                              |                 |
|---------------------------------------------|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Toxic Substances Control Act - TSCA         | 9AKK108467A8326 |

| Environmental             |                                    |
|---------------------------|------------------------------------|
| Environmental Information | 1SDL000183R0001<br>9AKK108467A6707 |
| REACH Declaration         | 9AKK108466A1425                    |
| RoHS Information          | 9AKK108466A1424                    |



|                                                                   |                   |
|-------------------------------------------------------------------|-------------------|
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> ) | (240 V AC) 100 kA |
|                                                                   | (380 V AC) 36 kA  |
|                                                                   | (415 V AC) 36 kA  |
|                                                                   | (440 V AC) 25 kA  |
|                                                                   | (480 V AC) 18 kA  |
|                                                                   | (500 V AC) 10 kA  |
|                                                                   | (250 V DC) 10 kA  |
| Rated Uninterrupted Current (I <sub>u</sub> )                     | 125 A             |
| Release                                                           | TMF               |
| Release Type                                                      | TM                |
| Short-Circuit Performance Level                                   | N                 |
| Standards                                                         | IEC               |
| Sub-type                                                          | A1                |
| Terminal Connection Type                                          | Front             |
| Version                                                           | F                 |

Certificates and Declarations

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC210032D0204 |
| Declaration of Conformity - CE    | 9AKK106713A5519 |
| Wiring Diagram                    | 1SDM000067R0001 |
| Instructions and Manuals          | 1SDH000717R0001 |

Classifications

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                     | V11.1 : 27370409                                                             |

Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Formula DSA

