# **Product datasheet**

Specification





# Easy9 RCD with overcurrent protection - 1P + N - 25 A - C curve - 6000 A - 10 mA

EZ9D16625

### Main

Range	Easy9
Product Or Component Type	Residual current breaker with overcurrent protection (RCBO)
Device Short Name	Easy9 RCBO
Poles	1P + N
Neutral Position	Left
[In] Rated Current	25 A
Network Type	AC
Trip Unit Technology	Thermal-magnetic
Curve Code	С
Earth-Leakage Sensitivity	10 mA
Earth-Leakage Protection Time Delay	Instantaneous
Earth-Leakage Protection Class	Type A
Breaking Capacity	6000 A Icn at 230 V AC 50 Hz conforming to IEC 61009-1
Suitability For Isolation	Yes

## Complementary

Device Application	Distribution
Device Location In System	Outgoer
[Ue] Rated Operational Voltage	230 V AC 50 Hz
Magnetic Tripping Limit	510 x ln
Limitation Class	3
[Ui] Rated Insulation Voltage	400 V AC 50 Hz
[Uimp] Rated Impulse Withstand Voltage	4 kV
Contact Position Indicator	Yes
Control Type	Toggle
Local Signalling	ON/OFF indication
Mounting Support	DIN rail
Mounting Mode	Clip-on
Comb Busbar And Distribution Block Compatibility	YES
9 Mm Pitches	2
Height	93 mm

Width	18 mm
Depth	70 mm
Net Weight	136 g
Colour	White
Mechanical Durability	20000 cycles
Electrical Durability	10000 cycles
Locking Options Description	ON/OFF locking facilities
Connections - Terminals	Tunnel type terminal (upstream) 116 mm² rigid Tunnel type terminal (downstream) 110 mm² rigid Tunnel type terminal (upstream) 116 mm² flexible Tunnel type terminal (downstream) 110 mm² flexible
Wire Stripping Length	11 mm for downstream connection 13 mm for upstream connection
Tightening Torque	2 N.m upstream 2 N.m downstream
Earth-Leakage Protection	Integrated

## **Environment**

Standards	IEC 61009-2-2 IEC 61009-1
Tropicalisation	2
Relative Humidity	95 % at 55 °C
Ambient Air Temperature For Operation	-2555 °C
Ambient Air Temperature For Storage	-2570 °C

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7 cm
Package 1 Width	1.8 cm
Package 1 Length	9.6 cm
Package 1 Weight	141 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	12
Package 2 Height	8 cm
Package 2 Width	10 cm
Package 2 Length	22 cm
Package 2 Weight	1.59 kg
Unit Type Of Package 3	S03
Number Of Units In Package 3	72
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	10.17 kg



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations