



shunt trip (spring) MX - 24 V AC 50/60Hz - 24 V DC

LV426841

Main

Range	ComPact
Range Of Product	ComPacT NSXm new generation
Device Short Name	MX
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Opening coil Shunt trip release
Control Type	Standard
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz 24 V DC
Range Compatibility	ComPact ComPacT NSXm new generation ComPact ComPact NSXm PowerPact PowerPact B

Complementary

Operating Threshold	0.7 Un opening
Response Time	< 50 ms
Control Signal Type	Impulse Maintained
Impulse Duration	>= 20 ms
Auxiliary Connection Terminal	Spring

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	5.7 cm
Package 1 Length	6.3 cm
Package 1 Weight	36.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	120
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm

Package 2 Weight

8.5 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information