# **Product datasheet**

Specification





# iCT 16A 2NO 230...240V 50Hz contactor

Local distributor code: 396735160

A9C22712

EAN Code: 3606480097058

#### Main

Range Of Product	Acti9
Product Name	Acti9 iCT
Product Or Component Type	Contactor
Device Short Name	iCT
Device Application	Motor-heating-lighting
Poles	2P
[le] Rated Operational Current	16 A AC-7A 6 A AC-7B
Pole Contact Composition	2 NO
Network Type	AC
Control Type	Remote control
[Uc] Control Circuit Voltage	230240 V AC 50 Hz

### Complementary

Network Frequency	FO.U-
	50 Hz
[Ue] Rated Operational Voltage	250 V AC 50 Hz
Maximum Power	1.2 W at 250 V AC
[Ui] Rated Insulation Voltage	500 V AC 50 Hz
[Uimp] Rated Impulse Withstand Voltage	4 kV
Control Signal Type	Maintained
Switching Frequency	100 switching operations/day
Local Signalling	Action indicator
Hold-In Power Consumption In Va	2.7 VA
Inrush Power In Va	9.2 VA
Mounting Mode	Clip-on
Mounting Support	35 mm symmetrical DIN rail
9 Mm Pitches	2
Height	81 mm
Width	18 mm
Depth	68.5 mm
Colour	White

Mechanical Durability	1000000 cycles	
Electrical Durability	100000 cycles IEC/EN 61095 16 A 50 Hz AC-7A	
	30000 cycles IEC/EN 61095 6 A 50 Hz AC-7B	
	30000 cycles IEC/EN 61095 50 Hz AC-7C	
	100000 cycles EN/IEC 60947-4-1 50 Hz AC-1	
	30000 cycles EN/IEC 60947-4-1 50 Hz AC-3	
	30000 cycles EN/IEC 60947-4-1 50 Hz AC-5a	
	30000 cycles EN/IEC 60947-4-1 50 Hz AC-5b	
Connections - Terminals	Control circuit: tunnel type terminals2 cable(s) 1.5 mm² rigid	
	Power circuit: tunnel type terminals1 cable(s) 14 mm² flexible	
	Power circuit: tunnel type terminals1 cable(s) 1.56 mm² rigid	
	Control circuit: tunnel type terminals1 cable(s) 1.52.5 mm² rigid	
	Control circuit: tunnel type terminals2 cable(s) 1.52.5 mm² flexible	
Tightening Torque	Control circuit: 0.8 N.m	
	Power circuit: 0.8 N.m	
Product Compatibility	IACTs	
Compatibility Code	ICT	
Market Segment	Small commercial	
	Residential	

### **Environment**

Standards	IEC/EN 61095
Noise Level	30 dB
Heat Dissipation	0.9 W at 50/60 Hz
Ip Degree Of Protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution Degree	2
Tropicalisation	2 conforming to IEC 60068-1 2
Relative Humidity	95 % at 55 °C
Operating Altitude	2000 m
Ambient Air Temperature For Operation	-560 °C
Ambient Air Temperature For Storage	-4070 °C

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	1.800 cm
Package 1 Length	8.300 cm
Package 1 Weight	116.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	12
Package 2 Height	2.850 cm
Package 2 Width	30.000 cm
Package 2 Length	20.000 cm
Package 2 Weight	1.445 kg
Unit Type Of Package 3	S03

Number Of Units In Package 3	144
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	17.779 kg

## **Contractual warranty**

Warranty 18 months

## Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations